

## Alltek UK – Specification for Plaster Board

### Plasterboard Walls & Ceilings.

1. Tape and joint the wall & ceiling Boards and dab out the screw/nail heads using either a powder or ready mixed joint filler, leave material flush with joint. Alltek Lite+ is a suitable Ready mixed Product. Ensure the material is left flush with the surface of the board.
2. Fill in any large gaps or damaged areas. - Fix paper tape around internal corners between ceiling and wall bedding in with the joint filler, around window reveals use the metal backed Flex tape or a thin joint angle bead and bed in with a powder or Alltek Lite+ ready mixed joint filler.
3. Prior to spraying, remove any raised area of filler with 120 grade sand paper.
4. Spray ceilings with Alltek Red, Violet or Alltek Orange, a two coat application is recommended. After applying the first coat level material off with a spatula, leave to dry. Repeat this process on all the walls. Spray or Hand apply to the window reveals. Leave to dry. **NB. Alltek Violet is the best material for achieving a textured Finish.**
5. Apply second coat to ceiling (12-24 hours), if a textured effect is required no further action is required, if a smooth finish is required level smooth with a spatula. When a textured finish is left a smooth border can be placed around the edge with a 40/50mm brush. Repeat this process for the walls apart from the border. Where a textured effect is required window reveals will need to be masked prior to application, if smooth finish is required repeat as per the first coat. NB. Textured finishes require no further decoration and Alltek Violet will achieve the best results for texture finishes.
6. When dry, lightly sand any raised areas with a 120/160 grade sand paper and apply one full coat of emulsion. **NB. Textured/Decorative ceilings do not require painting.**
7. Both Air and Airless machines can be used to achieve the required finish/results.
8. A trained 2 man team should complete between 800 – 1000 m2 per week.
9. NB. Alltek can be supplied in a range of pre mixed pastel shades, simply provide a RAL or NCS colour code and we will manufacture to that colour. A minimum of 3 tonnes is required for pre coloured materials. (1000 - 1200m2 Coverage)

